PORTABLE DUST COLLECTOR



24,000 CFM Diesel Unit



MODEL DC24LPDH

Specifications

85000016A (Rev. 08/13)

Capacity • 24,000 CFM. @ 13" W.G. Static Pressure

20,000 CFM @ 16" W.G. Static Pressure

• Carbon Steel Construction With Top Removal Filter Design

 Pleated Polyester Filter Elements, Vertically Hung, For Natural Release Of Dust

• Efficiency: 99.9% + 2 Mi cron (.015 Grains/ACF)

• 4380 Sq. Ft. Media Area

• Air-To-Cloth Ratio: 5.48:1 @ 24,000 CFM

4.57:1 @ 20,000 CFM

Pulse System For Continuous Cleaning

6" Diameter Air Manifold With Pressure Gauge, Regulator

And Drain Valve

• 12 VDC Solenoids With Solid State Timer Control In

NEMA 4 Enclosure

• Air Requirements; 24 CFM, Clean, Dry Compressed Air @

80 PSIG Clean, Dry, Oil Free Air

Ducting Connections • Two – Tapered Inlet Connections At Rear For 24"

Diameter Duct Connection

• Caterpillar or Equal, Tier III Flex Diesel Power Unit

V-Belt Drives Fan With Clutch / PTO

• 55-Gallon Fuel Tank (8 or more Hours of Operation)

Dust Disposal
Discharges Into 55 Gallon Drum With Drum Lid And High

Level Indicator (Drums Are By Others)

Dust Removal Conveyor

• 9" Size Main Auger and 6" Size Swivel Discharge Auger

With Hydraulic Motor Drives



Options

Skid Mount

• 8-1/2' Wide x 21-1/2' Long x 10' High, Weight - 12,500 Lbs

Trailer Mount

- 8-1/2' Wide x 25' Long x 10-1/2' High, Weight 14,500 Lbs
- Dual 10,000 Lb. Tandem Axles With Electric Brakes On Both Axles, Safety Chains, Leveling Jack, Running Lights, Reflectors, and Pintle Hook Tow Connection



